

Specpoint

www.specpointsystems.com
P.O. Box 11279 • Yakima, Washington 98909
(509) 965-9253

SPECPOINT UVH20 A-D SERIES



Overview

- Features high performance U.V. sensing technology
- The industry's most reliable and accurate with over 10,000 systems operating worldwide
- Exclusive 100% passive sampling
- Closed or open process sampling
- No electrochemical sensor cell to replace

Specifications*

- Accuracy +/- .50% of range
- Repeatability +/- .10% of range
- Measurement Ranges:
 - 0-50 PPM
 - 0-100 PPM
 - 0-200 PPM
 - 0-500 PPM NH₃
- Display type analog meter (digital optional)
- PV out: 4-20 ma or 1-5 vdc
- One alarm trouble relay S.P.S.T. 5 amps / 120 vac
- One alarm relay 3.P.D.T. 5 amps / 120 vac
- Power requirement: 120 volt AC 60HZ 10 VA
- Sample flow requirement: 5-25 SCFH
- Dimensions: 8"l x 8"w x 36"h
- Electrical Enclosure: NEMA 12
- UL CSA (Pending)
- Optional Feature: Multi-point sample sequencer (up to 8 zones)

**Manufacturer reserves the right to change specs without notice*

Applications

- Cold Storage and Controlled Atmosphere (CA) warehouse ammonia detection
- Mechanical room ammonia detection
- Process monitoring of ammonia
- Specialized industry solutions
- Detection of other gases (Contact us for details)

Specpoint Systems, LLC manufactures new instrument systems and replacement parts for Honeywell UVH series ammonia detectors.

Specpoint

www.specpointsystems.com
P.O. Box 11279 • Yakima, Washington 98909
(509) 965-9253

SPECPOINT UVH22 A-D SERIES



Overview

Features high performance U.V. sensing technology
The industry's most reliable and accurate with over 10,000 systems operating worldwide
Exclusive 100% passive sampling
Closed or open process sampling
No electrochemical sensor cell to replace

Specifications*

Dual-range, same, or mixed-range
Accuracy +/- .50% of range
Repeatability +/- .10% of range
Measurement Ranges:
0-50 PPM
0-100 PPM
0-200 PPM
0-500 PPM NH₃
Display type analog meter (digital optional)
PV out: 4-20 ma or 1-5 vdc
One alarm trouble relay S.P.S.T. 5 amps / 120 vac
One alarm relay 3.P.D.T. 5 amps / 120 vac
Power requirement: 120 volt AC 60HZ 10 VA
Sample flow requirement: 5-25 SCFH
Dimensions: 8"l x 8"w x 36"h
Electrical Enclosure: NEMA 12
UL CSA (Pending)
Optional Feature: Multi-point sample sequencer (up to 8 zones)

**Manufacturer reserves the right to change specs without notice*

Applications

Cold Storage and Controlled Atmosphere (CA) warehouse ammonia detection
Mechanical room ammonia detection
Process monitoring of ammonia
Specialized industry solutions
Detection of other gases (Contact us for details)

Specpoint Systems, LLC manufactures new instrument systems and replacement parts for Honeywell UVH series ammonia detectors.